

**In the Claims:**

The status of the claims is as follows:

1. (Previously presented) A display device employing a field-sequential method, comprising:

a light source having a plurality of colors of emitted light;

a light emission switching unit for sequentially switching the plurality of colors of emitted light of said light source within one frame;

a light switching element for controlling an intensity of light from said light source for display;

a control unit for controlling synchronization of a light-emission timing of each color of emitted light of said light source and a switching of said light switching element; and

a frame number changing unit for changing a frame number per unit time; wherein

said control unit controls the synchronization of the light emission timing and the switching in accordance with the frame number changed by said frame number changing unit.

2. (Original) The display device of claim 1, wherein  
said frame number changing unit comprises a discrimination circuit for  
judging whether display data is motion picture data or still picture data, and a changing  
circuit for changing the frame number per unit time based on a result of the judgement by  
said discrimination circuit.

3. (Original) The display device of claim 2, wherein  
when the display data is motion picture data, the frame number per unit  
time is increased compared with the frame number for still picture data.

4. (Original) The display device of claim 1, wherein  
said frame number changing unit comprises a detector for detecting a  
temperature of said light switching element, and a changing circuit for changing the frame  
number per unit time based on a result of the detection by said detector.

5. (Original) The display device of claim 4, wherein  
when the temperature of said light switching element is higher than a  
predetermined temperature, the frame number per unit time is increased compared with the  
frame number for a temperature lower than said predetermined temperature.

6. (Original) The display device of claim 1, wherein  
said light switching element is a liquid crystal display element.
7. (Original) The display device of claim 2, wherein  
said light switching element is a liquid crystal display element.
8. (Original) The display device of claim 4, wherein  
said light switching element is a liquid crystal display element.
9. (Original) The display device of claim 6, wherein  
said liquid crystal display element includes a liquid crystal material  
having spontaneous polarization.
10. (Original) The display device of claim 7, wherein  
said liquid crystal display element includes a liquid crystal material  
having spontaneous polarization.
11. (Original) The display device of claim 8, wherein  
said liquid crystal display element includes a liquid crystal material  
having spontaneous polarization.

12. (Original) The display device of claim 6, wherein  
said liquid crystal display element comprises an active element  
corresponding to each of a plurality of liquid crystal pixels.

13. (Original) The display device of claim 7, wherein  
said liquid crystal display element comprises an active element  
corresponding to each of a plurality of liquid crystal pixels.

14. (Original) The display device of claim 8, wherein  
said liquid crystal display element comprises an active element  
corresponding to each of a plurality of liquid crystal pixels.

15. (Original) The display device of claim 9, wherein  
said liquid crystal display element comprises an active element  
corresponding to each of a plurality of liquid crystal pixels.

16. (Original) The display device of claim 10, wherein  
said liquid crystal display element comprises an active element  
corresponding to each of a plurality of liquid crystal pixels.

17. (Original) The display device of claim 11, wherein  
said liquid crystal display element comprises an active element  
corresponding to each of a plurality of liquid crystal pixels.

18. (Previously presented) A display device employing a field-  
sequential method for displaying a color image by sequentially switching a plurality of colors  
of emitted light of a light source within one frame and by synchronizing a light-emission  
timing of each color of emitted light with a switching of a light switching element for  
controlling an intensity of light for display, comprising:

a changing unit for changing a frame number per unit time; and

a control unit for controlling the synchronization of the light-emission  
timing and the switching in accordance with the frame number changed by said changing  
unit.

19. (Previously presented) A field-sequential display method for  
displaying a color image by sequentially switching a plurality of colors of emitted light of a  
light source within one frame and by synchronizing a light-emission timing of each color of  
emitted light with a switching of a light switching element for controlling an intensity of light  
from said light source for display, comprising:

judging whether image data is motion picture data or still picture data;  
and  
changing a frame number per unit time based on a result of the  
judgement; and  
controlling the synchronization of the light-emission timing and the  
switching in accordance with the changed frame number.

20. (Previously presented) A field-sequential display method for  
displaying a color image by sequentially switching a plurality of colors of emitted light of a  
light source within one frame and by synchronizing a light-emission timing of each color of  
emitted light with a switching of a light switching element for controlling an intensity of light  
from said light source for display, comprising:

detecting a temperature of said light switching element; and  
changing a frame number per unit time based on a result of the  
detection; and  
controlling the synchronization of the light-emission timing and the  
switching in accordance with the changed frame number.